



Applied Panels

Integrating applied panels into your designs transforms the aesthetics and simplifies installation, while offering a practical solution in case of damage.

ADVANTAGES

- **The addition of applied panels instead of finished sides allows:**
 - Changing the appearance of your designs.
 - Creating a “framed” or “inset” look by surrounding your furniture with panels.
- **Simplifies adjustment:**
 - Easier to adjust against a wall than an entire piece of furniture.
- **Simplifies replacement:**
 - In case of damage, simply replace the panel instead of the entire piece of furniture.
- **Simplifies installation:**
 - The installer can use either side of the panel.
 - Simplifies handling of cabinets since they do not have finished sides.

OPTIONS

M01.

Thicknesses available: 3/4 inch or 1 1/2 inches for all products.

M02.

Thicknesses available: 3/4 inch or 1 1/2 inches for all products, and a 1/2 inch thickness available for certain products.



Note: Applied panels will be the only option available in the M02 collection; the “finished side” option is not available.

Applied Panels

TIPS



ON SITE: If necessary, order oversized panels for better adjustment.



COLOR UNIFORMITY: With laminates, using panels instead of finished sides ensures a uniform color inside your cabinets.



FLUSH DOOR: If the applied panels must be installed flush with the doors, order them finished on both sides.



INVISIBLE APPLIED PANELS: To achieve this, order your panels flush with the cabinet and add an extension to the module door to hide it.



ALIGN PERFECTLY WITH THE DOOR: The width of the panel should be equal to the depth of the cabinet + the thickness of the door + the thickness of the bumper.

HOW TO ORDER IN EM2 (There are two alternatives)

OPTION 1 | APPLIED PANELS

01.

Add a applied panels.
The panel must be finished on both sides as it is installed "flush door."

02.

Calculate the size of the panel that will cover the sides of the cabinets.
Make sure to add the thickness of the door and bumper.

03.

Choose the desired panel thickness:
Choices: 1/2, 3/4, or 1 1/2 inches.

OPTION 2 | FALSE DOOR (D01)

01.

Add "False Door" (D01).
Instead of choosing the finished sides option.

02.

Choose the false door option.
This item will automatically be the same model as the cabinet doors.

03.

Verify the dimensions.
The false door will have the exact dimension of the cabinet side plus the thickness of the door and its cushion.



Note: The false door is always shipped separately and not installed on the cabinet.

TRAINING AVAILABLE AT THE FAC



- **30 min. Miralis**—Available in the Partners Zone in the FAC section.
 - Collection M02 – Products and cabinets.
 - Design with applied panels.
- To register for the training, contact the FAC via fac@miralis.com.